

## Label Information

The Spectrum label presents technical and safety information in an easily understood format. Our technical specialists stay abreast of the latest requirements of the Globally Harmonized System for Classification and Labelling of Chemicals (GHS), as well as the Occupational Safety and Health Administration (OSHA), the Food and Drug Administration (FDA) and other government regulatory agencies in order to ensure compliance, accuracy and concise hazard communication. Below you will find a typical label example for this catalog item.

Exp. Date: 00-00-0000



**USE CARE:** This material has been evaluated per GHS/OSHA criteria and is not classified as hazardous. All chemicals may pose unknown hazards and must be used with caution. Use personal protection and safe handling methods consistent with proper workplace safety practices. Consult SDS for additional properties and precautions. If adverse reaction occurs seek medical attention.

**KEEP FROM CHILDREN**

**CA159**

**SIZ SY**

### Calcium Pantothenate

Powder, USP

CAS 137-08-6



**CAUTION:** For manufacturing, processing or repacking. Read and understand the label and Safety Data Sheet (SDS) prior to use.

**Chemical Emergency: (800)424-9300**

[www.SpectrumChemical.com](http://www.SpectrumChemical.com)

$C_{18}H_{32}CaN_2O_{10}$  F.W. 476.53

Assay (Dried Basis) .....	98.0-102.0%
Calcium Content (Ca; Dried Basis) .....	8.2-8.6%
Optical Rotation .....	+25.0° to +27.5°
MAXIMUM LIMITS	
Loss on Drying .....	5.0%
Alkalinity .....	To pass test
Elemental Impurities .....	As reported
Residual Solvents .....	To pass test

LIGHT SENSITIVE, HYGROSCOPIC: Keep tightly closed in light-resistant containers.

FLUSHED WITH NITROGEN

**WARNING:** Cancer and Reproductive Harm-  
[www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

G 13/H1GHS ? Lot No. XQ####

### Spectrum Chemical Mfg Corp

**Corporate Headquarters:**

769 Jersey Ave.  
New Brunswick, NJ 08901

732.214.1300

**West Coast Facility:**

14422 S. San Pedro St.  
Gardena, CA 90248

310.516.8000